



Connection Zindagi Ka

SOLAR

SOLAR GRID-TIE 50KW & 60KW STRING INVERTERS

THREE PHASE



LEADING FEATURES

- Transformerless Inverter
- Maximum Efficiency Over 98.9%, EU Efficiency Over 98.5%
- Wide MPPT Voltage Range with 4 MPPT Design and Precise MPPT Algorithm
- IP 65 Certified
- Low Harmonic Distortion, THDi < 3%
- Integrated DC Switch
- Intelligent Fan-Cooling
- 5 Years Standard Warranty With Extended Warranty Option
- Onboard SPDs For DC & AC Sides
- Free Remote Monitoring on Web Portal & Mobile App

SOLAR GRID-TIE STRING INVERTERS

TECHNICAL SPECIFICATIONS		
MODEL	PSIT - 50K	PSIT - 60K
Rating	50 KW	60 KW
INPUT SIDE (DC)		
Max. DC Input Power (kW)	60	72
Max. DC Input Voltage (V)	1100	
Start-up Voltage (V)	200	
MPPT Voltage Range (V)	200-1000	
Max. Input Current (A)	28.5A+28.5A+28.5A+28.5A	
Max Short Circuit Current for each MPPT (A)	44.5+44.5+44.5+44.5	
MPPT Number / No. of Strings per MPPT	4/3	
OUTPUT SIDE (AC)		
Rated Output Power (kW)	50	60
Max. Apparent Output Power (kVA)	55	66
Max. Output Power (kW)	55	66
Rated Grid Voltage (V)	400	400
Grid Voltage Range (V)	304-460	304-460
Rated Grid Frequency (Hz)	50/60	
Operation Phase	Three	
Rated Grid Output Current (A)	72.2	86.6
Max. Output Current (A)	83.3	100
Power Factor (at Rated Output power)	0.8 leading ..1.. 0.8 lagging	
THDi (at Rated Output Power)	<3%	
DC Injection Current	<0.5% In	
Grid Frequency Range (Hz)	47-52 or 57-62	
EFFICIENCY		
Max. Efficiency	98.80%	99.00%
EU Efficiency	98.40%	98.50%
MPPT Efficiency	> 99.90%	
PROTECTIONS		
Built-in Protections	DC Reverse-Polarity Protection, Short Circuit Protection, Output over Current Protection, Output Over Voltage Protection, Insulation Resistance Monitoring, Residual Current Detection, Surge Protection & Monitoring, Islanding Protection, Temperature Protection, surge protection through SPDs on both AC and DC sides, Grid Monitoring	
Integrated DC switch	YES	
GENERAL DATA		
Dimensions (mm)	630W*700H*357D (mm)	
Weight (kg)	63	
Topology	Transformerless	
Self Consumption (Night)	<1W(Night)	
Operating Ambient Temperature Range	- 25° to 60° C	
Ingress Protection	IP 65	
Noise Remission {Typical}	<60 dBA	
Cooling Concept	Intelligent Fan-Cooling	
Max. Operation Altitude	4000m	
Design Life	>20Years	
Relative Humidity	0~100%	
FEATURES		
DC Connection	MC-4Mateable	
AC Connection	OT Terminal Connectors	
Display	LCD,2x20 Z	
Communication Connections	4 Pins RS485 Connector, 2 RJ45 Connector, 2 Group of Terminal Block	
Monitoring Interface	LAN / Wifi / GPRS	
IEC CERTIFICATES		
Grid Connection	IEC 61727	
Anti - Islanding Protection	IEC 62116	
Environmental Testing	IEC 60068-2 (1-2-14-27-30-64)	
Safety	IEC 62109-1, IEC 62109-2, EN 62109-1, EN 62109-2	
EMC	IEC 61000, EN 61000-6-2, EN 61000-6-4	
Efficiency Measurement	IEC 61683, EN 50530	

Note: Specifications are subject to change


POLYCARB INDIA LIMITED (formerly known as Polycab Wires Limited)
 Polycab house, 771 Mogul lane, Mahim (W), Mumbai 400 016. Email: solar@polycab.com | Web: www.polycab.com

For Consumer Complaint Contact : Officer, Consumer Care Cell
 Polycab House, 771, Mogul Lane, Mahim (W), Mumbai 400 016, Maharashtra, India.
 Tel: 91-22-2432 7070 - 4,6735 1400 | Fax: 91-22-24327075
 Email: customercare@polycab.com | Website: www.polycab.com | Toll Free No.: 1800 267 0008

Solar Division Marketing Office:

POLYCARB INDIA LIMITED (formerly known as Polycab Wires Limited)
 Off. No. 34, Sangam Project Phase-2, Near RTO Pune,
 Near Sangam Bridge, Pune- 411001.

Follow us on:



Authorised Distributor / Dealer